



SHOW UP Aerosol Instructions

Usage Instructions

Thoroughly remove any dirt, oil, rust, wax, etc., from the surface to be painted.

Perform surface preparation and apply various primers or surfacers if necessary.

Shake the container well before use to ensure thorough mixing.

Avoid painting on days with high humidity.

When spraying paint, keep the can 15 to 30 cm away from the surface and spray parallel to it.

Apply the paint in thin layers rather than thick layers all at once, waiting 2-3 minutes between each coat.

Once the paint is used up, release the gas until the hissing sound stops, then dispose of it according to your local regulations.

Maziora Aerosol - Outer Coating (for Model Kits)

1. Apply Base color Real Black Aerosol (PC Binder Aerosol) until the surface is completely covered.
2. After Base color Real Black Aerosol is dry, apply Maziora Aerosol until the desired color is achieved (typically 6-8 coats).
3. Once Maziora Aerosol is dry, apply top coat using PC Binder Clear Aerosol.

Maziora Aerosol - Inner Coating (for Polycarbonate Bodies)

1. Apply thin layer of PC Binder Clear Aerosol approximately twice.
2. After PC Binder Aerosol has dried, apply Maziora Aerosol until the desired color is achieved (typically 6-8 coats).
3. Once Maziora Aerosol is dry, back paint with PC Binder Black Aerosol.

※ For outer coating (model kits) using Maziora Aerosol, PC Binder Black Aerosol can also be used as a substitute for Base color Real Black Aerosol.

Caution

- Ensure adequate ventilation as this product contains organic solvents, and keep it away from open flames.
- Work in an area where it is acceptable for paint to scatter.
- Excessive application can damage plastic materials such as polycarbonate and polystyrene, causing melting or cracks.
- Insufficient drying of PC Binder may result in paint cracking or poor adhesion, so ensure it is completely dry before proceeding to the next step.

Storage Precautions

- To prevent the can from rusting, never store it in damp or humid places.
- Do not store in cars, near heaters, in places with sparks, or areas that can exceed 40°C.
- To prevent nozzle clogging, after use, hold the container upside down, press the button for 1-2 seconds to spray out the residual paint, and wipe the nozzle thoroughly with a cloth.
- Store leftover paint with the cap on, avoiding direct sunlight, and keep it out of reach of children to prevent tampering.